



Product Code

UTC-0398E	Portable Slump Test Set, EN
UTC-0400E	Slump Test Set, EN
UTC-0402E	Slump Cone, EN
UTC-0404E	Slump Base Plate 500x500x60 mm with Handle, EN
UTC-0406	Slump Cone Funnel, Galvanized Steel
UTC-0408	Tamping Rod Ø 16x600 mm
UTC-0410	Tamping Rod Ø10x300 mm
UTGH-1605	Round Scoop, Medium
UTGM-0380	Steel Ruler 300x1 mm

Standards

EN 12350-2

The Slump test method is used for the determination of the consistency and workability of fresh concrete.

UTC-0398E and UTC-0400E Slump Test Sets are supplied galvanized to prevent corrosion.

All parts of the Portable Slump Test Set (UTC-0398E) can be carried together easily.



The Slump Test Set are supplied complete with;

- Slump Cone Top Dia: 100 ±2 mm / Base Dia: 200 ±2 mm / Height: 300 ±2 mm / Thickness 1,5mm
- Slump Base Plate 500x500x60 mm with Handle (with UTC-0400E)
- Slump Base Plate with Handle and Clamps (with UTC-0398E)
- Slump Funnel, Galvanized Steel
- Tamping Rod Ø 16x600 mm
- Round Scoop, medium
- Steel Ruler 300x1 mm

Dimensions	550x560x310 mm (packed)
Weight (approx.)	6 kg