

Product Code

UTA-0620A	Micro-Deval Apparatus, ASTM
UTA-0621A	Stainless Steel Jar, ASTM, for UTA-620A
UTA-0623A	Micro-Deval Abrasion Charges, ASTM, Ø9,5 mm 2 pcs. of 6 kg Packed

Models for 220-240V 50 Hz, 1 ph.	UTA-0620A-T
Models for 110-120V 60 Hz, 1 ph.	UTC-0620A-N
Models for 220-240V 60 Hz, 1 ph.	UTC-0620A-K

Standards

ASTM D6928, D7428; AASHTO T327

The Micro Deval Testing Machine is used to determine the resistance to wear of aggregates.

The machine consists of a steel frame, two stainless steel jar stainless steel spheres (2 pcs) and an automatic digital counter which allows machine to stop automatically at the preset number of revolutions.

Stainless steel jars are rotating at a speed of 100 ± 5 r.p.m.

1,18 mm sieve should be ordered separately.

UTA-0620A Micro-Deval Apparatus is supplied complete with;

- Stainless Steel Jar, ASTM, 2 pcs.
- Abrasion Charges, ASTM, Ø9,5 mm, 2 pcs. of 6 kg packed

Dimensions	450x1260x980 mm
Weight (approx.)	105 kg
Power	550 W

