UNIAXIAL & TRIAXIAL TESTS

Product Code

UTR-0455	Hoek Triaxial Cell BX (42.04 mm dia.)
UTR-0456	Spare Sealing Sleeves, BX (42,04 mm dia.) for Hoek Triaxial Cell
UTR-0463	Hoek Triaxial Cell NQ (47,6 mm dia.)
UTR-0464	Spare Sealing Sleeves, NQ (47.6 mm dia.) for Hoek Triaxial Cell
UTR-0457	Hoek Triaxial Cell NX (54.74 mm dia.)
UTR-0458	Spare Sealing Sleeves, NX (54,74 mm dia.) for Hoek Triaxial Cell
UTR-0460	Hoek Triaxial Cell HQ (63,5 mm dia.)
UTR-0461	Spare Sealing Sleeves, HQ (63,5 mm dia.) for Hoek Triaxial Cell

Standards

ASTM D5407; ASTM D7012

Hoek Cells have been designed to be used for triaxial testing of rock specimens.

Hoek Cells comprise a steel body complete with two quick release self-sealing couplings for oil inlet and outlet, two steel end caps which are screwed to the cell body, a rubber sealing sleeve to separate the specimen from the cell fluid, two female spherical seated coupling with loading caps and two male spherical seated coupling with load spreading heads.

	Dimensions	Weight (approx.)
UTR-0455	350x150x200 mm	15 kg
UTR-0457	350x150x200 mm	15 kg
UTR-0460	350x150x200 mm	15 kg
UTR-0463	350x150x200 mm	15 kg