TEMPERATURE & TIME MEASUREMENT

Product Code

UTGT-1205	Digital Thermometer Immersion Type -50°C to +300°C
UTGT-1230	Digital Max-Min Thermometer -40 to +50°C
UTGT-1240	Digital Thermo-Hygrometer, Max-Min Thermometer
UTGT-1250	Digital Laser Thermometer -50°C to +650°C
UTGT-1300	Glass Thermometer Max. 60°C
UTGT-1305	Glass Thermometer Max. 110°C
UTGT-1310	Glass Thermometer Max. 160°C
UTGT-1315	Glass Thermometer Max. 250°C
UTGT-1320	Glass Thermometer Max. 310°C
UTGT-1325	Glass Thermometer Max. 360°C
UTGT-1330	Glass Thermometer Max. 400°C
UTGT-1350	Hand Type Digital Thermometer, -50°C to 1350°C
UTGT-1352	Temperature Datalogger, 4 Channel Digital Display
UTGT-1355	Connector, Type: OMTS-K-E for UTGT-1350
UTGT-1360	Cable, Type: E-0,5 T2KTTEA. Meter for UTGT-1350
UTGT-1370	200 mm Penetration Probe for Asphalt Tempereture Mesurement
UTGT-1371	300 mm Penetration Probe for Asphalt Tempereture Mesurement
UTGT-1372	500 mm Penetration Probe for Asphalt Tempereture Mesurement

UTEST supplies high quality digital and glass thermometers for various applications in the construction industry.

UTGT-1350, UTGT-1352, UTGT-1355 ve UTGT-1360 are used for monotoring of temperature development of mass concrete. The number of measurement points for connectors and the cable length needed for each measurement point should be indicated. The products should be ordered seperately.

UTGT-1352 4 Channel Digital Display Temperature Datalogger is an alternative to UTGT-1350 and can record continuously in the time interval selected by the user. The datalogger has -195°C to +1000°C temp. measurement range for K Type sensors, 1s – 24h data record range and 2 million data recording capacity. Battery operated data logger is supplied comğplete with acceessories such as cable for connecting to PC, software, SD card (for collecting the measurement).

Digital thermometer and penetration probes are used together for measuring the delivery and compaction temperatures of bituminous mixtures. Preffered penetration probe should be ordered with UTGT- 1350.

UTGT-1230

UTGT-1352

CAUTION

Please check the laws in your country before ordering mercury thermometers. There may restriction on their sale and shipment for the thermometers contains mercury.

UTGT-1205

UTGT-1250

Glass Thermometers

UTGT-1240

Product Code	Dimensions	Weight
UTGT-1205	150x150x150 mm	0.2 kg
UTGT-1230	150x150x150 mm	0.2 kg
UTGT-1240	150x150x150 mm	0.2 kg
UTGT-1250	100x100x100 mm	0.2 kg
UTGT-1300	30x30x300 mm	0.1 kg
UTGT-1305	30x30x300 mm	0.1 kg
UTGT-1310	30x30x300 mm	0.1 kg
UTGT-1315	30x30x300 mm	0.1 kg
UTGT-1320	30x30x300 mm	0.1 kg
UTGT-1325	30x30x300 mm	0.1 kg
UTGT-1330	30x30x300 mm	0.1 kg
UTGT-1350	150x80x40	0.3 kg
UTGT-1352	150x80x40	0.3 kg
UTGT-1355	20x10x5	0.01 kg
UTGT-1360	100x100x5	0.01 kg
UTGT-1370	350x50x30	0.5 kg
UTGT-1371	400x50x30	0.5 kg
UTGT-1372	650x50x30	0.6 kg