

### Product Code

|           |                                                          |
|-----------|----------------------------------------------------------|
| UTGT-1430 | Viscosity Thermometer +19 to +27°C 0.1°C Div., ASTM 17C  |
| UTGT-1432 | Viscosity Thermometer +34 to +42°C 0.1°C Div., ASTM 18C  |
| UTGT-1434 | Viscosity Thermometer +49 to +57°C 0.1°C Div., ASTM 19C  |
| UTGT-1436 | Viscosity Thermometer +57 to +65°C 0.1°C Div., ASTM 20C  |
| UTGT-1438 | Viscosity Thermometer +79 to +87°C 0.1°C Div., ASTM 21C  |
| UTGT-1440 | Viscosity Thermometer +95 to +103°C 0.1°C Div., ASTM 22C |
| UTGT-1500 | Mechanical Hygrometer/Thermometer/Barometer              |
| UTGT-1520 | Mechanical Hygrometer                                    |
| UTGT-1550 | Mechanical Dial Thermometer 0 to +260°C                  |
| UTGT-1580 | Digital Stop Watch                                       |

UTEST Viscosity Thermometers are used for UTAS-0300 Saybolt Two-Tube Digital Viscometer in order to determine the Saybolt Viscosity of petroleum products at specified temperatures where accurate temperature measurements are required.

UTGT-1500 Mechanical Hygrometer/Thermometer/Barometer is a reliable and useful instrument to monitor the humidity, temperature and the atmospheric pressure simultaneously.

UTGT-1520 Mechanical Hygrometer is reliable instrument for measuring the humidity of the ambient air and UTGT- 1550 Mechanical Dial Thermometer provides accurate temperature measurements especially at high temperatures up to 260°C.

UTGT-1580 Digital Stop Watch is designed for accurate time measurements with 0.01 second sensitivity.



Viscosity Thermometers



UTGT-1520



UTGT-1550



UTGT-1500



UTGT-1580

| Product Code | Description                                    | ASTM Ref. | IP Ref. | Dimensions     | Weight |
|--------------|------------------------------------------------|-----------|---------|----------------|--------|
| UTGT-1430    | Viscosity Thermometer +19 to +27°C 0.1°C Div.  | 17 C      | -       | 30x30x300 mm   | 0.1 kg |
| UTGT-1432    | Viscosity Thermometer +34 to +42°C 0.1°C Div.  | 18 C      | 23 C    | 30x30x300 mm   | 0.1 kg |
| UTGT-1434    | Viscosity Thermometer +49 to +57°C 0.1°C Div.  | 19 C      | -       | 30x30x300 mm   | 0.1 kg |
| UTGT-1436    | Viscosity Thermometer +57 to +65°C 0.1°C Div.  | 20 C      | -       | 30x30x300 mm   | 0.1 kg |
| UTGT-1438    | Viscosity Thermometer +79 to +87°C 0.1°C Div.  | 21 C      | -       | 30x30x300 mm   | 0.1 kg |
| UTGT-1440    | Viscosity Thermometer +95 to +103°C 0.1°C Div. | 22 C      | 24 C    | 30x30x300 mm   | 0.1 kg |
| UTGT-1500    | Mechanical Hygrometer/Thermometer/Barometer    | -         | -       | 150x150x150 mm | 0.2 kg |
| UTGT-1520    | Mechanical Hygrometer                          | -         | -       | 150x150x150 mm | 0.2 kg |
| UTGT-1550    | Mechanical Dial Thermometer 0 to +260°C        | -         | -       | 50x50x200 mm   | 0.2 kg |
| UTGT-1580    | Digital Stop Watch                             | -         | -       | 75x65x25 mm    | 0.1 kg |